



# Inspirations® Bottled Water Cooler

*IB 110 NLEZ  
IB 210 NLEZ*

*IW 110 NLEZ  
IW 210 NLEZ*



## Features

- 2.0L / .53G stainless steel hot tank with all SS fittings between hot and cold tanks
- 3.8L / 1G polished stainless steel cold tank with laser welded joints and seams
- A new “D” shaped copper evaporator tubing means one side of the tubing is flat... creating more contact and more surface area with the cold tank which improves cold water performance.
- Evaporator copper tubing thickness is increased by 33%, providing longer life and resistance to “pin” hole refrigerant leaks.
- Water is dispensed through industry standard Tomlinson style faucets that allow for Hot and Cold or Cook and Cold options
- Removable, two-piece drip tray for easy cleaning
- Easily converts from bottled water to filtration (POU)
- No external base plate
- Cup dispenser (option)
- Available in black and white
- Energy Star rated hot tank with On/Off switch
- UL listed
- **No Leak® EZ-Fill®** - Patented no-spill adapter for use with no-spill bottle caps



*Reliably Serving A Thirsty World*



## Power

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.44A / 118W 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (kWh/24 hrs.)	0.86
% lower than ES Standard	1%

## Hot Water System

Avg. Hot Water Temp at Nozzle @ 77 °F Ambient (Cut-in / Cut-out Temp)	167 °F +/- 9 °F / 187 °F +/- 4 °F
Hot Water ARI Rating	45, 6 oz. > 165 °F +/- 10%
Hot Thermometer / Heat Limiter	203 °F +/- 5.5 °F
Hot Thermostat / Thermistor Cycle	167 °F +/- 9 °F / 187 °F +/- 4 °F
Hot Water Flow Rate	0.67 - 0.73 oz./sec
Hot Tank Size (L)	2.0L
Heat Band Wattage	450W

## Cold Water System

Avg. Cold Water Temp at Nozzle @ 75 °F Ambient (Cut-in / Cut-out Temp)	45.87 °F / 42.2 °F
Cold Water ARI Rating	45, 5 oz. > 50 °F +/- 10%
Cold Thermostat Set Point	45 °F + 3 °F/-8 °F
Cold Water Flow Rate	1.4 oz./sec
Cold Tank Size / Usable Volume / Below Base Cold Water (Liter : Gallon)	3.78 / 2.08 / 1.51 : 1 / 0.55 / 0.4

## Weights and Measurements

Net Weight (H&C / C&C Lbs.)	31 / 27
Gross Weight (H&C / C&C Lbs.)	33 / 30
Max Distance from Drip Tray to Faucet (Inch : mm)	7.8 : 199
Faucet / Dispense Height (Inch : mm)	28.75 : 730.25
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.4x13.78x42.91 / 13x13.9x43.9
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL Listed

### Warranty:

3 years: Sealed refrigeration system  
2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

email: [chris@mywaterquy.ca](mailto:chris@mywaterquy.ca)

phone: 519-637-3306

web: [www.mywaterquy.ca](http://www.mywaterquy.ca)

Available at



**Simply Pure  
Water**  
The LOCAL Water Experts